

BS 10 Table Flanges

TABLE H

For Working Steam Pressure above 150 lbs and upto 250 lbs per sq. Inch

Nominal Pipe Size	O. D. of pipe	O. D.	P. C. D.	No. of bolt	Dia of bolt	Thickness
1/2"	21.3	114.3	82.6	4	15.9	12.7
3/4"	26.7	114.3	82.6	4	15.9	12.7
1"	33.4	120.7	87.3	4	15.9	14.3
1.1/4"	42.2	133.4	98.4	4	15.9	17.5
1.1/2"	48.3	139.7	104.8	4	15.9	17.5
2"	60.3	165.1	127.0	4	15.9	19.1
2.1/2"	73.0	184.2	146.1	8	15.9	19.1
3"	88.9	203.2	165.1	8	15.9	22.2
3.1/2"	101.6	215.9	177.8	8	15.9	22.2
4"	114.3	228.6	190.5	8	15.9	25.4
5"	141.3	279.4	235.0	8	19.1	28.6
6"	168.3	304.8	260.4	12	19.1	28.6
7"	190.5	336.6	292.1	12	19.1	31.8
8"	219.1	368.3	323.9	12	19.1	31.8
9"	244.5	406.4	355.6	12	22.2	34.9
10"	273.0	431.8	381.0	12	22.2	34.9
12"	323.9	489.0	438.2	16	22.2	38.1
14"	355.6	552.5	495.3	16	25.4	41.3
16"	406.4	609.6	552.5	20	25.4	44.5
18"	457.2	673.1	609.6	20	28.6	47.6
20"	508.0	736.6	673.1	24	28.6	50.8
24"	609.6	850.9	781.1	24	31.8	57.2

Information in this catalog was compiled from industry sources that Tech Tubes & Fitting believes to be reliable.

We, however, do not guarantee the accuracy of this data.

ALL DIMENSIONS IN INCHES